

COCKERILL® CPWS



Multi-mission
Protected
Light



Defense America

a John Cockerill company

johncockerillda.com • johncockerill.com/defense

COCKERILL® CPWS

Protected loading



Technical specification

Vehicle Integration	4x4 & 6x6 Light Armored Vehicles
Turret	Welded Ballistic aluminium with innovative roof structure
Main Armament	25x137 mm – 30x113 mm
Crew	Operated by one operator
Secondary Armament	7.62 mm
Ammunition loading	Single/dual feeder with a minimum of 155 ready-rounds and the capability to reload under armour
Anti-Tank	Turret launched AT systems
Elevation	-10° to +60°
D/R/I	APC : up to 6800/2600/1400 Reconnaissance : up to 11500/4900/2500
Ballistic protection	Up to Level 5 STANAG 4569
Protection	4 smoke grenade launchers
Sight	One sight system : <ul style="list-style-type: none"> ▪ panoramic ▪ linked to the cannon

Multi-Configuration



Closed = Full protected



*Elevated = Manned/Observation/
Surveillance/Sniping*



*Removed = OOTW
(Operations Other Than War)*



Fully Open = Evacuation



Missile Launcher



30 mm

Multi-Cannon 25-30

a  John Cockerill company

info@johncockerillda.com